



Premium Quality Safes You Can Trust



FORTIFIED BY
THE REAL
SANDY SPRINGS
LOCKSMITH™
SAFES AND SECURITY
-404-256-3780-
SERVING METRO ATLANTA 24/7
SINCE 1965



The Finest Fire and Burglary Protection Available Anywhere in the World!

Gardall designs and manufactures fire and burglary resistive safes to meet or exceed many different standards and specifications.

Standard Safe Classifications

To understand how our safes are classified, here is a brief explanation of the labels you'll find on them.

Fire Protection – Two-Hour 1850° or One-Hour 1700°

Gardall fire-resistive safes meet or exceed Underwriters' Laboratories specifications for explosion, fire endurance and drop tests.

Two-Hour exposure to severe fire with an exterior temperature to 1850°F, and an interior temperature that does not exceed 350°F (paper chars at 405°F) for two hours and cool down.



One-Hour exposure to severe fire with an exterior temperature to 1700°F, and an interior temperature that does not exceed 350°F (paper chars at 405°F) for one hour and cool down.



Residential Security Container Burglary Label

Gardall's 2-Hour Burglary Fire (pg. 2) and FB (pg. 6) models have passed the U.L.-R.S.C. label test for burglary protection.



Burglary Protection

Gardall safes with the Class "B" or Class "C" Burglary Insurance Rating allow you to receive insurance coverage in accordance with the Broad Form and Mercantile Safe Insurance classifications. Pertinent insurance information is available from Insurance Service Office, 160 Water Street, New York, NY 10038.

Gardall safes can be supplied with an Underwriters' Laboratory Group II combination lock, U.L. listed key-op lock, U.L. listed dual key lock or a U.L. listed push button electronic lock.

Gardall Lifetime Replacement Warranty

Gardall Safe Corporation assures to the original end consumer, replacement – free of charge – of any Gardall Fire-Resistive Record Safe damaged beyond repair by fire with a then-current production model of a comparable value. This warranty is exclusive and in lieu of any warranty of merchantability, fitness for particular purpose or other warranties of qualities, whether expressed or implied, and of all other liabilities and obligations on the manufacturer's part.

Gardall Safe Corporation reserves the right to inspect any record safe prior to replacement. Copies of insurance reports or documents pertaining to fire loss will be furnished to Gardall Safe Corporation upon request.

Gardall Safe Corporation specifically assumes no liability for installation or other charges incurred by the owner in connection with the replacement of any record safe and assumes no liability for damage to contents or personal property contained in any such file or any consequential damages of any nature or description.



**Your Best Protection
Against Fire or Theft**

Visit us online at
www.gardall.com
MADE IN THE U.S.A.

These Gardall fire resistive safes are designed and tested to withstand severe fire with outside temperatures reaching 1750°F for two hours. Safe interior temperatures will not exceed 350°F within two hours. The charring of paper occurs at 405°F. All Gardall fire resistive safes provide a comfortable margin that protects your valuables. But these models don't stop at just fire protection. They also have Class "B" burglary resistive features built in right at the factory.

And don't forget, every fire insurance policy states that "proof of loss" is required for claims. When your business or personnel inventories are locked inside a Gardall fire resistive safe, your "proof of loss" is protected 24 hours a day, 7 days a week.



Standard Features

- Five active locking bolts in a three-way configuration
- Three plated deadbolts extend into safe wall preventing entry if hinges are removed.
- Hard plate between the lock and dial ring.
- Independent relocking device designed to stop forced entry or drill attacks
- UL listed, Group II combination lock
- Heavy duty casters to allow the safe to be positioned easily (welded on)
- **Gardall Lifetime Replacement Warranty** (see inside front cover)

Manufacturers 2-Hour Fire Label

A safe similar in construction was tested by an independent testing facility. The furnace temperature reached 1750°F for a period of time exceeding 2 hours, before the interior of the safe reached 350°F.

Lock Options

- Push Button Electronic
- Mechanical Combination
- Single Key (Key-op)

Standard colors: Gray or sandstone.

The above mentioned Gardall fire resistive safes carry a 2-hour Manufacturers Fire Label.

All specifications are subject to change without notice.



| Model | Outside Dimensions | | | Inside Dimensions | | | Cubic Inches | Approx. Weight (lbs.) | Shelves |
|-------|--------------------|------|------|-------------------|------|------|--------------|-----------------------|---------|
| | H | W | D | H | W | D | | | |
| 3620 | 43½" | 25¾" | 26¾" | 36¼" | 20½" | 19½" | 14,490 | 804 | 3 |
| 4220 | 49½" | 25¾" | 26¾" | 42¼" | 20½" | 19½" | 16,890 | 871 | 3 |
| 4820 | 55½" | 25¾" | 26¾" | 48¼" | 20½" | 19½" | 19,285 | 975 | 4 |

Add 2" to outside depth for dial and handle.



Your Best Protection for
Media Against Fire or Theft

Visit us online at
www.gardall.com



With the growing number of homes and offices using computers, the protection of magnetic media has become extremely critical. The loss of personal as well as business records can be costly and devastating. The average fire safe is not designed to protect your electronic records. Gardall's media safes are designed to meet the additional requirements of protecting magnetic media. For your convenience we offer two sizes to choose from.

Standard Features

- Push button electronic lock with key day lock
- 3 way bolt work with bolt detent
- Push button electronic lock – 6-digit combo
- One or two removable shelves (model dependent)
- No anchoring holes
- Key operated day lock
- **Gardall Lifetime Replacement Warranty** (see inside front cover)

Protect Your Electronic Media

- Office Computer Back-Ups
- Home Computer Back-Ups
- Digital Pictures
- Music CDs
- DVDs
- Video Tapes
- One-hour fire protection for media products
- 150°F Fire Label

| Model | Outside Dimensions | | | Inside Dimensions | | | Approx. Weight (lbs.) | Shelves |
|--------------|--------------------|------|------|-------------------|------|------|-----------------------|---------|
| | H | W | D | H | W | D | | |
| EDS1210-G-EK | 21½" | 19½" | 18½" | 10⅞" | 9" | 7¼" | 209 | 1 |
| EDS2214-G-EK | 31½" | 23¼" | 20" | 20¾" | 12½" | 15¼" | 374 | 2 |

Add 1½" to outside depth for dial and handle. No bolt-down hole in these models.



**Gardall Microwave Safes...
Premium Quality You Can Trust**

Visit us online at
www.gardall.com



Microwave Safes

- One-hour fire safe label*
- Four compact sizes
- Center bolt down (hardware included)
- Single key or push button electronic locks for easy opening
- Programmable electronic lock with over-ride code
- Individual packaging for UPS type shipping
- Powder coated paint for increased durability
- Pull-out tray for storage of small items
- **Gardall Lifetime Replacement Warranty** (see inside front cover)

Gardall offers a full range of U.L. approved fire resistive microwave style safes. These safes are made to Gardall's exact specifications and brought to you with the same care and quality you have come to expect from Gardall. Microwave style safes come with either a single key or electronic style lock. All fire safes have plated interlocking bolts that extend into the safe walls to prevent tampering and removal of doors. The doors are precision built of extra heavy steel, full swinging on heavy duty hinges with interlocking, tongue and groove closure on all sides of the door frame. All safes come with a center bolt down hole and hardware to anchor the safe down.

| Model | Outside Dimensions | | | Inside Dimensions | | | Approx. Wt. (lbs.) | Description |
|--------------|--------------------|------|------|-------------------|------|------|--------------------|--|
| | H | W | D | H | W | D | | |
| MS911-G-K | 11½" | 15¼" | 12½" | 8½" | 12" | 8½" | 61 | Horizontal 1 Hr Fire Safe with Single Key Lock |
| MS911-G-E | 11½" | 15¼" | 12½" | 9½" | 12" | 8½" | 61 | Vertical 1 Hr Fire Safe with Electronic Lock |
| * MS912-G-K | 13½" | 16¾" | 15¼" | 9½" | 12¾" | 10¼" | 85 | Horizontal 1 Hr Fire Safe with Single Key Lock |
| * MS912-G-E | 13½" | 16¾" | 15¼" | 9½" | 12¾" | 10¼" | 85 | Horizontal 1 Hr Fire Safe with Electronic Lock |
| * MS129-G-K | 16¾" | 13½" | 15¼" | 12¾" | 9½" | 10¼" | 85 | Vertical 1 Hr Fire Safe with Single Key Lock |
| * MS129-G-E | 16¾" | 13½" | 15¼" | 12¾" | 9½" | 10¼" | 85 | Vertical 1 Hr Fire Safe with Electronic Lock |
| * SS1612-G-K | 20½" | 16¼" | 17½" | 16½" | 11½" | 12" | 140 | Vertical 1 Hr Fire Safe with Single Key Lock |
| * ES1612-G-E | 20½" | 16¼" | 17½" | 16½" | 11½" | 12" | 143 | Vertical 1 Hr Fire Safe with Electronic Lock |

* U.L. 350°F One-Hour Label – Fire and Impact Test *Add 1½" to outside depth for dial and handle.*



Gardall's Heavy Duty Depositories

Visit us online at
www.gardall.com
 MADE IN THE U.S.A.



Designed to protect money collection where immediate deposit is required. Deposit can be made into the safe while the door is locked. Exclusive baffle design prevents contents from being removed through the entry opening. Hopper rotor is built into safe body and cannot be removed to gain access to the safe.

Heavy Duty Depositories Standard Design Benefits

- CLASS B Insurance Rating – 1/2" steel door with punch resistant bolt and relocking device to deter forcible entry. 1/4" steel body construction.
- Dual Custody Key Locks – Requires 2 keys to open door for absolute security.
- UL listed, Group II combination lock.
- Triple boltwork with independent relocking device.
- Relocking device – If back cover is knocked off of lock, the independent relock device is activated, preventing bolt withdrawal. Available on either combination or dual key operated doors.

- Rotary Hopper Capacity – 3¾" x 9" x 4" designed to fit most standard money bags and envelopes.
- Front Loading Capacity – designed to fit most large money bags – 2¾" x 10½" x 7½"
- 4 anchoring holes in base.

Standard color: Gray

All specifications are subject to change without notice.

To Operate Front Loading Depository

Pull drop door forward, place items to be deposited inside, release the drop door.

Deposited item should drop inside.

Open the drop door to be certain.



| Model | Outside Dimensions | | | Inside Dimensions | | | Inside Cubic Inches | Door Size | Approx. Weight (lbs.) | |
|---------|--------------------|------|-----|-------------------|------|------|---------------------|-----------|-----------------------|-----|
| | H | W | D | H | W | D | | | | |
| GFL1328 | 25" | 14½" | 13" | 15" | 13½" | 11½" | 2329 | 12"x12" | 165 | |
| BL1328 | 25" | 14½" | 13" | 15" | 13½" | 11½" | 2329 | 12"x12" | 132 | |
| GFL1337 | 36½" | 14½" | 13" | T | 12" | 13½" | 10¾" | 3592 | 12"x12" | 200 |
| | | | | B | 14¾" | 13¾" | 10¾" | 2180 | | |
| RC1237 | 36¾" | 14½" | 13" | T | 15¼" | 13¾" | 10¾" | 2180 | 12"x12" | 220 |
| | | | | B | 14¾" | 13¾" | 10¾" | 2180 | | |
| *BL1337 | 36½" | 14½" | 13" | T | 12" | 13½" | 10¾" | 1742 | 12"x12" | 215 |
| | | | | B | 14¾" | 13¾" | 10¾" | 2180 | | |

Above available as (K) dual key lock (C) Group II combination lock, (KO) key-op lock or (E) electronic lock. Please specify.

*BL designates depository on back side of safe from door. Add 2" to outside depth for dial and handle.

IMPORTANT! These safes are built with the intent of keeping large bills and valuables out of unprotected areas, until deposits can be made. They are not meant to be used as unprotected storage safes for overnight, or lengthy periods of time. Discuss your needs with your local safe professional or if you are in doubt, call GARDALL and we will recommend a safe expert.



**Your Best Protection
Against Fire and Theft**



Designed for complete protection of your valuables, a “B” rated burglary safe securely welded inside a 2-hour fire resistive safe.



Safe/Chest Combo
TL15 Chest with
2 Hour Fire Safe below



Standard Features

- Class “B” Rated interior safe construction. Door of inner safe will interchange with other Gardall safes key lock or combination.
- Fire Resistive Exterior Safe – Insulated to withstand 1850°F for 2 hours.
- UL listed, Group II combination lock
- Relocking Device – If back cover is knocked off of the lock, the independent relock device is activated, preventing bolt withdrawal.
- Boltwork Interior Door – Triple boltwork with independent relock device (except Models 1812 and 1818).
- Boltwork Exterior Door – Interlocking bolts extend into the safe walls, deadbolts on hinge side of door to deter forcible entry by removal of hinges.
- Hard plate on both interior and exterior door.
- Available with electronic push-button lock.



**Your Best Protection
Against Robbery and Fire**

Visit us online at
www.gardall.com



Gardall Safe Corporation has been manufacturing premium quality safes for home and office applications since 1950. Our Commercial High Security safes are manufactured to specifications which are more stringent than many of our competitors requirements. Some of the standard features on Gardall TL15 and TL30 safes are options with other manufacturers. Please be sure to compare our specifications with those of our competitors before making your decision.

- **UL TL15** – Tool Resistant for 15 minutes
- **UL TL30** – Tool Resistant for 30 minutes
- **UL TL30X6** – Tool Resistant for 30 minutes all six sides of safe.

Standard Features:

Door Construction:

- **TL15** – 5½" slab High Density Fiber Reinforced Material
- **TL30** – 5½" overall, 3" slab of High Density Fiber Reinforced Barrier Material – TDRII*
- **TL30x6** – TL30x6 – 5½" overall thickness with 2" Defense Barrier

Body Construction:

- **TL15** – 2½" slab of High Density Barrier Material
- **TL30** – 2½" slab of High Density Barrier Material
- **TL30x6** – 2½" thick composite Reinforced Manganese steel armor plate

Anti Burglary Components:

- Cross locking relockers.
- Punch resistant spindle handle and lock.
- Tempered glass relocking trigger.
- Bridge mounted lock.
- Formed 1/8" stainless steel locking bar 1½" depth.

Locks:

- Group 2M listed combination. Key lock available for dual custody.

Hinges:

- Massive heavy duty adjustable ball bearing hinges.

Fire Rating:

- Fire tested to 1850°F. Interior temperature less than 350°F for 1 hour.